

- ▶ Compatible with Locating Systems
- ▶ Detects Water, Acid and Corrosive Chemical Liquids
- ▶ Pre-connected in Standard Lengths
- ▶ Unique Dust-Proof Feature Efficiently Preventing False Alarms

## Description

The TTK sense cable FG-ACX detects the presence of water, acid and corrosive chemical liquids at any point along its length. The FG-ACX sense cable connects to TTK's analog alarms (FG-ALS8, FG-ALS4 & FG-A), to respond immediately in the event of any leaks of liquids. The TTK Sense Cable FG-ACX is available in standard, pre-finished lengths of 9, 22 and 49 ft (3, 7 or 15 m) complete with connectors.

## Features & Benefits

### A RELIABLE SENSE CABLE

The FG-ACX sense cable performs the following functions:

- Rapidly detects the leak of acid or corrosive chemical liquid along the length of the cable.
- Detects leaks the nearest metre when connected to the Locating Alarm Units: FG-ALS8 and FG-ALS4.
- Detects any break or cut to the cable.
- Ingenious design: four sensing wires of helical construction, compressed and connected on an extruded central core, **efficiently prevent false alarms** that have been triggered by **dust and all kinds of conductive residue** from the environment that has accumulated on the cable surface.

### A MODULAR SYSTEM

The FG-ACX cable ensures permanent protection in areas at risk. FG-

ACX is available in standard and pre-finished lengths of 9, 22 and 49 ft (3, 7 and 15 m). The sense cable is installed to provide the best possible protection in order to cover risks and limit the financial consequences of an undetected leak.

### EASY INSTALLATION

The male and female connectors at the end of each length of FG-ACX cable give immediate and dependable connection.

Fixing clips are used to fasten the sense cables in the chosen areas.


### A TOUGH AND STURDY DESIGN

Small in diameter, the FG-ACS sense cable is light, flexible and of an easily identifiable color. The FG-AC sense cable is a non-absorbent design that **can be reused** after cleaning, reducing the maintenance costs.

## Technical Data

Compatibility	Alarm units: FG-ALS8, FG-ALS4, FG-A
Maximum Rated Temperature	185°F (85°C)
Minimum Bend Radius	0.79 in (20 mm)
Weight	0.017 lb/ft (25g/m)
Sense Cable Diameter	0.29 in (7.5 mm) with PVDF jacket
Liquid Quantity to Active Alarm	1.97 - 3.94 in (50-100 mm) on the sense cable
FG-ACX Color	Green and white

# Product Diagram



## Technical Information

A= The cable resists in the presence of the liquid considered.  
B= The cable resists, but undergoes a slow corrosion.

In all cases where a leak is detected, it is advisable to identify the source of the leak and to repair the leak quickly. In most cases the contaminated FG-ACX cable can be washed and re-used.  
This list is not exhaustive, for other chemicals, specific concentrations or temperatures please consult with your TTK representative.

Acetic acid	A	Hydrochloric acid	B	Glucose	A
Alcohols	A	Benzene	A	Hydrocarbons	A
Ammoniac	B	Chloroform	A	Sea water	A
Nitric acid	A	Gasoline	A	Sodium sulfate	A
Silver nitrate	A	Ethanol	A	Sodium hydroxide	B
Hydrogen peroxide	A	Hydrofluoric acid	A	Salicylic acid	A
Carbonic acid	A	Formic acid	A	Sulphuric acid	A
Ferrous chloride	A	Freon	A	Toluene	A
Calcium carbonate	A	Tar	A	Potassium hydroxide	B

## Identification Codes

FG-ACX15	Analog acid sense cable in 15m (49 ft) length with connectors
FG-ACX7	Analog acid sense cable in 7m (22 ft) length with connectors
FG-ACX3	Analog acid sense cable in 3m (9 ft) length with connectors
Accessories	
FG-CLC	Leader cable in 11.5 ft (3.5 m) length
FG-TMX	End termination plug (for ECX, ACX sense cables)
CF-EC100	100 hold-down clips with cold adhesive glue
ES-EC	40 signal tags

## Certificate



This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this project. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use. FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2022

■ **TTK Headquarters** / 19, rue du Général Foy / 75008 Paris / France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / [www.ttk.fr](http://www.ttk.fr) / [ventes@ttk.fr](mailto:ventes@ttk.fr)  
■ **TTK UK Ltd.** / 3 Luke Street London EC2A 4PX / United Kingdom / T : 0207 729 6002 / F : 0207 729 6003 / [www.ttkuk.com](http://www.ttkuk.com) / [sales@ttkuk.com](mailto:sales@ttkuk.com)  
■ **TTK Pte Ltd.** / #09-05, Shenton House, 3 Shenton Way / Singapore 068805 / T : +65-6220.2068 / M : +65.9271.6191 / F : +65-6220.2026 / [www.ttk.sg](http://www.ttk.sg) / [sales@ttk.sg](mailto:sales@ttk.sg)  
■ **TTK Asia Ltd.** / 2107-2108 Kai Tak Commercial Building / 317 Des Voeux Road Central / Hongkong / T : +852.2858.7128 / F : +852.2858.8428 / [www.ttkasia.com](http://www.ttkasia.com) / [info@ttkasia.com](mailto:info@ttkasia.com)  
■ **TTK Middle East FZCO** / Building 6EA, Office 510 PO Box 54925 / Dubai Airport Free Zone / UAE / T : +971 4 70 17 553 / M : +971 50 259 66 29 / [www.ttkuk.com](http://www.ttkuk.com) / [cgalliche@ttk.fr](mailto:cgalliche@ttk.fr)  
■ **TTK Deutschland GmbH** / Berner Strasse 34 / 60437 Frankfurt / Deutschland / T : +49(0)69-95005630 / F : +49(0)69-95005640 / [www.ttk-gmbh.de](http://www.ttk-gmbh.de) / [vertrieb@ttk-gmbh.de](mailto:vertrieb@ttk-gmbh.de)  
■ **TTK North America Inc** / 1730 St Laurent Boulevard Suite 800 / Ottawa, ON, K1G 5L1 / Canada / T : +1 613 566 5968 / [www.ttkcanada.com](http://www.ttkcanada.com) / [info@ttkcanada.com](mailto:info@ttkcanada.com)  
■ **Thomas Sales & Marketing Inc. TTK Master Distributor For USA** / 7200 W 66th St / Bedford Park, IL 60638 / The United States / T : +1 630-518-4724 / [www.ttkusa.com](http://www.ttkusa.com) / [dmolk@ttkusa.com](mailto:dmolk@ttkusa.com)