



- Compatible with Locating Systems
- Unique Dust-Proof Feature Efficiently Preventing False Alarms
- Available in Standard Lengths

## Description

The TTK sense cable FG-ACS detects the presence of acids and water at any point along its length. The FG-ACS sense cable connects to TTK's locating units (FG-NET, FG-SYS, FG-ALS8 & FG-ALS4) or non-locating units (FG-A), to immediately respond to any leaks of acids and corrosive chemical liquids.

## Key Advantages

### A RELIABLE SENSE CABLE

The FG-ACS sense cable performs the following functions:

- Rapidly detects the leak of acids and water along the length of the cable.
- Detects and locates leaks when connected to a Locating Alarm Unit: FG-NET, FG-SYS, FG-ALS8 or FG-ALS4.
- Detects leaks when connected to a Non-locating Alarm Unit: FG-A.
- Detects any break or cut to the cable.
- Ingenious design: four sensing wires of helical construction, compressed and connected on an extruded central core, **efficiently prevent false alarms** that have been triggered by **dust and all kinds of conductive residue** from the environment that has accumulated on the cable surface.

### A MODULAR SYSTEM

The FG-ACS cable ensures permanent protection in areas at risk. FG-ACS is available in standard and pre-finished lengths of 9, 22 and 49

ft (3, 7, 15 m). The sense cable is installed to provide the best possible protection in order to cover risks and limit the financial consequences of an undetected acids leak.

### EASY INSTALLATION

A spliced junction with a length of 11.5 ft (3.5 m) of Plenum bus jumper cable and an end termination at each length of FG-ACS sense cable give immediate connection to the unit or to the sector diversion box.

Special fixing clips are used to fasten the sense cables in the chosen areas. A set of jumper cables and pre-finished connection accessories gives continuity to each circuit with the sector diversion box FG-DTCS.

### A TOUGH AND STURDY DESIGN

Small in diameter, the FG-ACS sense cable is light, flexible and of an easily identifiable color. The FG-ACS sense cable is a non-absorbent design that **can be reused** after cleaning in most cases, thereby reducing the maintenance costs.

## Technical Data

Compatibility	Locating units: FG-SYS, FG-NET, FG-BBOX (via Diversion Box: FG-DTCS, DCTL), FG-ALS8, FG-ALS4 Non-locating unit: FG-A
Reusability	Reusable, as long as the cable hasn't been damaged by prolonged immersion in liquid
Drying Time for Cable After Leak	Less than 10 seconds
Sense Cable Material & Nominal Diameter	PVDF, 0.3 in (± 0.02 in) (7.5 mm (± 0.5 mm))
Sensor Wires Material & Diameter	PVDF, 0.05 in (1.2 mm)
Core Material	PVDF
Sense Cable Weight (9, 22, 49 ft)	0.6 lb, 1.15 lb, 2.56 lb (0.27 kg, 0.52 kg, 1.16 kg)
Minimum Bend Radius	0.79 in (20 mm)
Sense Cable Color	Green and light gray
Operating Temperature	-40° to 185°F (-40° to 85°C)
Ingress Protection	IP 67

# Product Diagram

