

FG-ECX Water and Base Sense Cable

Product Datasheet



- ► Detects Water & Base Liquids
- ► Made with Low-halogen Materials
- Pre-connected in Standard Lengths

Description

The TTK Sense Cable FG-ECX detects the presence of conductive liquids at any point along its length. The FG-ECX sense cable can be connected to two kinds of TTK's alarm units: locating alarm unit and non-locating alarm unit. It detects and locates leaks to the nearest metre when connected to a locating alarm unit.

The sense cable FG-ECX is available in standard, pre-finished lengths of 9, 22 and 49 ft (3, 7 and 15 m) complete with connectors.

Each sense cable is manufactured with **low-halogen materials, limiting flame spread and smoke production**. This meets the requirements of the CPR regulation*.

*CPR (Construction Products Regulation) is a European Union regulation that aims to ensure the safety, durability, and performance of construction products, particularly in the event of fire, particularly with regard to flame spread and smoke production.

Key Advantages

A RELIABLE SENSE CABLE

The FG-ECX sense cable performs the following functions:

- Rapidly detects the leak of any liquid along the length of the cable.
- Detects and locates leaks to the nearest metre when connected to a locating unit.
- Detects leaks only when connected to a non-locating unit.
- Detects any break or cut to the cable.

Non-absorbant design can be reset in seconds after removal of the leak.

Manufactured using low-halogen materials, the FG-EC cable emits smoke with lower optical density and slower dispersion when exposed to high heat, compared to standard cables.

A MODULAR SYSTEM

The FG-ECX sense cable ensures permanent protection in areas at risk. FG-ECX is installed to provide the best possible protection in order to cover risks and limit the financial consequences of an undetected leak.

EASY INSTALLATION

The male and female connectors at the end of each length of FG-ECX cable give quick and dependable connection.

Fixing clips are used to fasten the sensing cables in the chosen areas.

A TOUGH AND STURDY DESIGN

Small in diameter, the FG-ECX sense cable is light, flexible and of an easily identifiable dark blue colour and yellow colour on male connector tip. Its helical jacket construction, compression connected on an extruded central core, reduces the risk of contamination and false alarms. It is made from the highest quality materials which are abrasive resistant in hostile environments.

Technical Data


| Compatibility | Alarm units: FG-ALS8, FG-ALS4, FG-A |
|---|--|
| Reusability | Reusable, as long as the cable hasn't been damaged by prolonged immersion in liquid |
| Drying Time for Cable After Leak | Less than 10 seconds |
| Sense Cable Nominal Diameter | 0.3 ± 0.02 in (7.5 ± 0.5 mm) |
| Central Core Material | LSZH based on PE |
| CPR (Construction Products Regulation) Classification | Dca: moderate performance, ensuring reliable performance in standard building applications |
| Minimum Bend Radius | 0.79 in (20 mm) |
| Color | Light blue |
| Operating Temperature | -40° to +185°F (-40° to +85°C) |
| Connector Ingress Protection | IP 67 |

FG-ECX Sense Cable



FG-ECX Sense Cable Cutting View

2 communication wires and 2 detection and location wires



Identification Codes

| FG-ECX3 | Analog Water Sense Cable in 9 ft (3 m) Length with Connectors |
|--------------|---|
| FG-ECX7 | Analog Water Sense Cable in 22 ft (7 m) Length with Connectors |
| FG-ECX15 | Analog Water Sense Cable in 49 ft (15 m) Length with Connectors |
| Accessories: | |
| FG-CLC | Leader Cable in 11.48 ft (3.5 m) Length |
| FG-TMX | Analog End Plug |
| FG-NC'N' | TTK Bus 8723 Neutral Cable 'N' (3, 33, 50 ft) (1, 10, 15 m) with Connectors |
| CF-EC100 | 100 Hold-down Clips with Adhesive for Water & Acids Cables |
| ES-EC | 40 Tags for Water & Acids Cables |

Certification



The FG-ECX cable meets Euroclass fire safety requirements and is classified Dca by UL Laboratory, ensuring reliable performance in standard building applications.

This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this project. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use. FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2025

- TTK USA Inc. / 100 S. Broad Street, Suite 730 Philadelphia, PA 19110 / Tel. +1 610 304 2270 / www.ttkusa.com / sales@ttkusa.com
- TTK Headquarters / 19, rue du Général Foy / 75008 Paris / France / T:+33.1.56.76.90.10 / F:+33.1.55.90.62.15 / www.ttk.fr / ventes@ttk.fr